

The Jazzy[®] 600 provides excellent performance and maximum stability. Its compact design and standard ATX Suspension allows it to excel indoors and out, making it a superb, all-around power chair choice.



Jazzy[®] 600 shown in *Candy Apple Red*

(US) 800-800-8586 • (Canada) 888-570-1113 Visit us on the web: www.pridemobility.com



SPECIFICATIONS	
Weight capacity	300 lbs.
Maximum speed	Up to 5 mph
Ground clearance	3"
Turning radius	20"
Overall length	36.5" without front riggings
Overall width	23"
Wheels	Drive: 14"
Front casters	5" solid OMNI-casters
Rear casters	6" solid OMNI-casters
Suspension	Active-Trac® ATX Suspension
Drive train	Two-motor, Mid-Wheel 6®
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	60 amp, PG VR2
Specialty controls	Yes (Group 3 only)
Battery charger	5 amp, off-board
Per-charge range	Up to 20 miles
Battery requirements	(2) 12 volt, deep cycle
Battery size	NF-22
Battery weight Base weight Standard seat weight	38 lbs. each 127 lbs. 37 lbs. (medium-back)
Max. seat dimensions	22" x 20"
Seat-to-floor range (high-back seat)	21" - 24"
Warranty	Lifetime limited warranty on frame; 2-year limited warranty on electronics; 18-month limited warranty on drive motors

MODELS

Jazzy 600 2S-C	Jazzy 600 3S-SS
Jazzy 600 2S-SS	Jazzy 600 3SP-C (250 lbs. capacity)
Jazzy 600 3S-C	Jazzy 600 3SP-SS (250 lbs. capacity)

FEATURES

- OMNI-Casters (nylon, spherical-shaped casters) on front and rear to prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- Active-Trac[®] ATX Suspension incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries

OPTIONS• Solid seat pan• Elevating leg rests• Cup holder• Oxygen tank holder• Swing-away joystick• Cane/crutch holder• Swing-away footrests• Walker holder• TRU-Balance® Power• Synergy® Seat

Tilt (Group 3 only)



COLOR CHOICES



800-800-8586 (US) • 888-570-1113 (Canada) Visit us on the web: www.pridemobility.com

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %.

